

simply **IPSO**[®]

On-Premises Laundry

IHF Series Washer-Extractor

On-premises laundries face enough daily challenges, wrestling with complicated, inefficient equipment shouldn't be one of them. IPSO's IHF model washer-extractors combine proven designs with user-friendly controls to streamline the laundry process. Our goal is building equipment that's simple to own and even more simple to operate.

Simplifying Ownership

VERSATILE. The PS40 microprocessor offers managers the highest level of control to set spin speeds and water levels, while a simple design ensures employees are quickly trained on its operation. It comes with 10 preprogrammed cycles and room to customize 30 additional cycles. Programming easily is accomplished by uploading from a PC through an infrared connection.

EFFICIENT. With a maximum extract of 475 G-Force, the IHF significantly reduces drying time — in some cases, by up to 40%. As a result, operations benefit from lower utility consumption.

RUGGED RELIABILITY. A heavy-duty steel frame, with a minimum of welds, provides one of the most stable bases in the market. That translates into years of worry-free operation. In addition, three layers of paint protect the frame from corrosion, while heavy-duty bearings and a rugged housing ensure longevity.

PEACE OF MIND. A 3-year parts warranty (5-years on major components) is standard.

WASHABILITY. While the IHF is designed to increase productivity and efficiency, managers don't have to sacrifice quality. IPSO washer-extractors deliver superior consistent finished results.



TIME SAVINGS. The IHF's automatic supply injection system — which supports up to 12 pumps — eliminates the need for staff to manually add chemicals. This saves time and allows them to concentrate on other laundry tasks. In addition, for laundries utilizing finishing equipment, the high extract speed of the IHF allows pieces to go directly from the washer to ironers with no drying necessary.

THE BOTTOM LINE. We believe the efficiency in design and operation of our washer-extractors combined with the features of our intuitive controls will have the ultimate impact on your laundry's productivity and bottom line. Put simply, IPSO gets results.

IHF033 - 33 lb Washer-Extractor
IHF045 - 45 lb Washer-Extractor
IHF055 - 55 lb Washer-Extractor
IHF075 - 75 lb Washer-Extractor
IHF100 - 100 lb Washer-Extractor
IHF135 - 135 lb Washer-Extractor
IHF165 - 165 lb Washer-Extractor



IHF Series Washer-Extractor Specifications

	IHF033	IHF045	IHF055	IHF075	IHF100	IHF135	IHF165							
Capacity - lb (kg)	33 (15.9)	45 (18.5)	55 (24.9)	75 (34.0)	100 (45.4)	135 (61.2)	165 (74.8)							
Height - in (mm)	54 3/16" (1376)	54 3/16" (1376)	60 3/16" (1528)	61 5/16" (1558)	75 9/16" (1920)	75 9/16" (1920)	82 11/16" (2100)							
Width - in (mm)	30 11/16" (780)	30 11/16" (780)	35 7/16" (900)	41 3/4" (1060)	47 1/4" (1200)	47 1/4" (1200)	51 1/4" (1300)							
Depth - in (mm)	33 1/16" (840)	37" (940)	39 3/16" (996)	45 1/8" (1147)	52 9/16" (1335)	59 1/16" (1500)	63 3/4" (1620)							
Door Opening - in (mm)	15 3/4" (400)	15 3/4" (400)	15 3/4" (400)	15 3/4" (400)	19 11/16" (500)	19 11/16" (500)	24 1/2" (622)							
Net Weight - lb (kg)	811 (368)	862 (391)	1177 (534)	1612 (731)	3351 (1520)	3627 (1645)	4630 (2100)							
Crated Weight - lb (kg)	844 (383)	921 (418)	1287 (584)	1722 (781)	3741 (1697)	4017 (1822)	5181 (2350)							
Cylinder Dimensions														
Diameter - in (mm)	26 3/4" (680)	26 3/4" (680)	29 1/2" (750)	33 7/16" (850)	38 9/16" (980)	38 9/16" (980)	43 1/8" (1095)							
Depth - in (mm)	15 3/4" (400)	19 11/16" (500)	20 7/8" (530)	21 1/8" (537)	23 1/2" (597)	30 1/2" (775)	30 1/2" (775)							
Volume - cu.ft. (liters)	5.12 (145)	6.39 (181)	8.26 (234)	10.74 (304)	16.07 (455)	20.31 (570)	25.78 (730)							
Cylinder Speed														
Wash - RPM	10-50	10-50	10-50	10-50	10-50	10-50	10-50							
Extract - RPM	250-1000	250-1000	250-1000	250-1000	500-800	500-800	500-750							
G-Force - RPM	380	380	419	475	350	350	350							
Drain Size - in (mm)	2" (50)	2" (50)	3" (75)	3" (75)	3" (75)	3" (75)	2 @ 4" (100)							
Water Inlet - (std/opt)	2/3	2/3	2/3	2/3	2/3	2/3	2/3							
Voltage/Hz/Phase														
Circuit Breaker - FLA														
(X)	200-240/50-60/1-3	20	200-240/50-60/1-3	20	200-240/50-60/1-3	30	200-240/50-60/1-3	30	200-240/50-60/1-3	N/A	200-240/50-60/1-3	N/A	200-240/50-60/1-3	N/A
(Q)	200-240/50-60/3	20	200-240/50-60/3	20	200-240/50-60/3	30	200-240/50-60/3	30	200-240/50-60/3	50	200-240/50-60/3	50	200-240/50-60/3	80
(P)	380-415/50-60/3	20	380-415/50-60/3	20	380-415/50-60/3	30	380-415/50-60/3	30	380-415/50-60/3	30	380-415/50-60/3	30	380-415/50-60/3	40
(N)	440-480/50-60/3	20	440-480/50-60/3	20	440-480/50-60/3	15	440-480/50-60/3	20	440-480/50-60/3	30	440-480/50-60/3	30	440-480/50-60/3	40
Agency Approvals	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}	CE, cETL _{US}


For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

©Copyright 2010 Alliance Laundry Systems LLC

Printed in the U.S.A.

Questions? Contact us at:
1 800 USA IPSO or www.ipso.com
1 800 (872-4776)

Control Options



PS40 Microprocessor