

simply **IPSO**[®]

On-Premises Laundry

IPH Series Washer-Extractor

On-premises laundries face enough daily challenges, wrestling with complicated, inefficient equipment shouldn't be one of them. IPSO IPH model washer-extractors combine proven designs with user-friendly controls to streamline the laundry process. Our goal is building equipment that's simple to own and even more simple to operate.

Simplifying Ownership

EFFICIENT TECHNOLOGY. Our SmartSpin™ technology features a maximum 300 G-Force extract on high-speed models, removes more water from loads and reduces drying times.



VERSATILE. The PS40 microprocessor offers managers the highest level of control to set spin speeds and water levels, while a simple design ensures employees are quickly trained on its operation. It comes with 10 preprogrammed cycles and room to customize 30 additional cycles. Programming is easily accomplished by uploading from a PC through an infrared connection.

RUGGED RELIABILITY. A heavy-duty steel frame, with a minimum of welds, provides one of the most stable bases on the market. That translates into years of worry-free operation.

VALUE. The high extract speeds of IPH washer-extractors can produce results similar to more expensive softmount units. Added value comes in the reduced utility consumption and time savings as drying times are decreased.

TIME SAVINGS. The IPH's automatic supply injection system eliminates the need for staff to manually add chemicals. This saves valuable minutes during a shift and allows employees to concentrate on other laundry tasks.

PEACE OF MIND. A 3-year parts warranty (5-years on major components) is standard.



WASHABILITY. While the IPH is designed to increase productivity and efficiency, managers don't have to sacrifice quality. IPSO washer-extractors deliver superior finished results.

THE BOTTOM LINE. We believe the efficiency in design and operation of our washer-extractors combined with the features of our intuitive controls will have the ultimate impact on your laundry's productivity and bottom line. Put simply, IPSO gets results.

IP040 - 40 lb Washer-Extractor
IP060 - 60 lb Washer-Extractor
IP080 - 80 lb Washer-Extractor
IP100 - 100 lb Washer-Extractor
IP125 - 125 lb Washer-Extractor
IP140 - 140 lb Washer-Extractor
IP175 - 175 lb Washer-Extractor



IPH Series Washer-Extractor Specifications

	IP040	IP060	IP080	IP100	IP125	IP140	IP175
Capacity - lb (kg)	40 (18)	60 (27)	80 (36)	100 (45)	125 (57)	140 (64)	175 (79)
Height - in (mm)	57" (1448)	62 5/8" (1590)	70" (1778)	70" (1778)	77 1/8" (1958)	77 1/8" (1958)	77 1/8" (1958)
Width - in (mm)	32" (813)	34 1/2" (876)	42 1/2" (1080)*	42 1/2" (1080)*	50 5/16" (1278)*	50 5/16" (1278)*	50 5/16" (1278)*
Depth - in (mm)	45 5/8" (1158)	47 13/16" (1214)	51 7/16" (1305)	56 7/16" (1432)	56 1/8" (1425)	59 1/8" (1501)	64 1/8" (1628)
Door Opening - in (mm)	15" (381)	17" (432)	20" (508)	20" (508)	24 1/2" (622)	24 1/2" (622)	28 1/2" (724)
Net Weight - lb (kg)	1690 (766)	1795 (814)	1926 (874)	2167 (983)	2749 (1247)	3027 (1373)	3277 (1486)
Crated Weight - lb (kg)	1770 (803)	1895 (859)	2026 (919)	2267 (1028)	2849 (1292)	3127 (1418)	3327 (1509)
Cylinder Dimensions							
Diameter - in (mm)	27" (686)	31" (787)	37" (940)	37" (940)	43" (1092)	43" (1092)	43" (1092)
Depth - in (mm)	19" (483)	22" (559)	21" (533)	26" (660)	24" (610)	27" (686)	32" (813)
Volume - cu.ft. (liters)	6.3 (178.3)	9.6 (271.7)	13.1 (370.7)	16.2 (458.5)	20.1 (569.2)	22.7 (642.4)	26.8 (759.9)
Cylinder Speed							
Wash - RPM	46	43	39	39	36	36	36
High Speed Models: Maximum Extract - RPM/G-Force	885/300	826/300	756/300	756/300	701/300	640/250	640/250
Medium Speed Models: Maximum Extract - RPM/G-Force	626/150	584/150	535/150	535/150	N/A	496/150	N/A
Drain Size - in (mm)	3" (76)	3" (76)	3" (76)	3" (76)	3" (76)	3" (76)	3" (76)
Water Inlet - (std/opt)	2/3	2/3	2/3	2/3	2/3	2/3	2/3
Voltage/Hz/Phase							
Circuit Breaker - FLA							
(Q)	208-240/50/60/3ph 15-7.5	208-240/50/60/3ph 20-11.7	208-240/50/60/3ph 30-15.5	208-240/50/60/3ph 30-15.5	208-240/50/60/3ph 30-21.1	208-240/50/60/3ph 30-21.1	N/A
(N)	380-480/50/60/3ph 15-3.9	380-480/50/60/3ph 15-6.2	380-480/50/60/3ph 20-8.1	380-480/50/60/3ph 20-8.1	380-480/50/60/3ph 20-11.1	380-480/50/60/3ph 20-11.1	380-480/50/60/3ph 20-13.3
Agency Approvals	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C	CE, ETL _{US} , ETL _C

* Add 6" to width for External Soap Dispenser (sidemount) on IP080 and larger models.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2000.

©Copyright 2011 Alliance Laundry Systems LLC

Printed in the U.S.A.

Questions? Contact us at:
1 800 USA IPSO or www.ipso.com
1 800 (872-4776)

Control Options



PS40 Microprocessor