## ON-PREMISES RIGID MOUNT WASHER EXTRACTOR



PA20 20lb





## **FEATURES**

- · Rigid mounted, 100 or 200 G-Force options
- Stainless steel top, front, and side panels
- · Stainless steel cylinder and tub
- Patented Cascade <sup>™</sup> cylinder for better washability
- XControl+ fully programmable control
- Patented soap hopper
- · Large drain valve
- Front access to vital parts for easy maintenance
- Large door opening for easy loading and unloading
- USB plug on the back panel and control board
- Warranty: First three years on all parts;
   First five years frame and cylinder shaft assembly; First five years on cylinder bearings and bearing seals (parts only)

## **OPTIONS**

- Third water inlet
- · Steam heating








LOW WATER AND ENERGY CONSUMPTION




WARRANT



MODEL	PA20
CONTROL OPTION	XControl+
CAPACITY - Ib (kg)	20 ( 8)
OVERALL WIDTH - in (mm)	25.98 (660)
OVERALL DEPTH - in (mm)	30.91 (785)
OVERALL HEIGHT - in (mm)	43 .89 (1115)
CYLINDER DIAMETER - in (mm)	20.87 (530)
CYLINDER VOLUME - cu. ft ( liters)	2.6 (75)
DOOR OPENING SIZE - in (mm)	13 (330)
DOOR BOTTOM TO FLOOR - in (mm)	13.74 (349)
WASH SPEED - RPM	50
EXTRACT SPEED - RPM	580/820
EXTRACT G-FORCE	100 or 200
STEAM HEATING - psi	15-116
SOUND PRESSURE LEVEL - dB (A)	< 65
WATER VALVE CONNECTION - NPT*	0.75"
WATER PRESSURE -psi	15-116
RECOMMENDED WATER PRESSURE - psi	44-73
WATER INLET (EACH) - g/min	5.28
DRAIN VALVE - in (mm)	3 (76)
FLOW AMOUNT W/ DRAIN VALVE - g/min	55.48
FLOOR TO DRAIN OUTLET CENTER - in (mm)	3.46 (88)
SIDE TO DRAIN OUTLET CENTER - in (mm)	6.53 (166)
STEAM VALVE CONNECTION - BSP	0.5"
VOLTAGE/CIRCUIT BREAKER - FLA 120/60/1	10-8.0
208-240/60/1	10-4.4
SHIPPING DIMENSIONS APPROX in (mm) Width	27.95 (710)
Depth	32.87 (835)
Height	49.02 (1245 )
NET WEIGHT - lb (kg)	298 (135)
SHIPPING WEIGHT - lb (kg)	320 (145)
AGENCY APPROVALS	cCSAus





DIMENSIONS		PA20
Α.	OVERALL WIDTH - in (mm)	25.98 (660 )
В.	OVERALL DEPTH - in (mm)	30.91 (785)
C.	OVERALL HEIGHT - in (mm)	43 .89 (1 115 )
D.	DOOR BOTTOM TO FLOOR - in (mm)	13.74 (349)