ON-PREMISES RIGID MOUNT WASHER EXTRACTOR



PA25 25lb



FEATURES

- Rigid mounted, 100 or 200 G-Force options
- Stainless steel top, front, and side panels
- Stainless steel cylinder and tub
- Patented Cascade [™] cylinder for better washability
- XControl+ fully programmable control
- Patented soap hopper
- Large drain valve
- Front access to vital parts for easy maintenance
- Large door opening for easy loading and unloading
- USB plug on the back panel and control board
- Warranty: First three years on all parts; First five years frame and cylinder shaft assembly; First five years on cylinder bearings and bearing seals (parts only)

OPTIONS

- Third water inlet
- Steam heating








Ideas for the future. Answers for today.®

1.877.755.5302 | www.coinamatic.com

MODEL	PA25
CONTROL OPTION	XControl+
CAPACITY - lb (kg)	25 (11)
OVERALL WIDTH - in (mm)	29.53 (750)
OVERALL DEPTH - in (mm)	30.91 (785)
OVERALL HEIGHT - in (mm)	48.22 (1225)
CYLINDER DIAMETER - in (mm)	24.4 (620)
CYLINDER VOLUME - cu. ft (liters)	3.7 (105)
DOOR OPENING SIZE - in (mm)	16.14 (410)
DOOR BOTTOM TO FLOOR - in (mm)	13.46 (342)
WASH SPEED - RPM	46
EXTRACT SPEED - RPM	540/760
EXTRACT G-FORCE	100 or 200
STEAM HEATING - psi	15-116
SOUND PRESSURE LEVEL - dB (A)	< 65
WATER VALVE CONNECTION - NPT*	0.75″
WATER PRESSURE -psi	15-116
RECOMMENDED WATER PRESSURE - psi	44-73
WATER INLET (EACH) - g/min	5.28
DRAIN VALVE - in (mm)	3 (76)
FLOW AMOUNT W/ DRAIN VALVE - g/min	55.48
FLOOR TO DRAIN OUTLET CENTER - in (mm)	3.85 (98)
SIDE TO DRAIN OUTLET CENTER - in (mm)	8.85 (225)
STEAM VALVE CONNECTION - BSP	0.5″
VOLTAGE/CIRCUIT BREAKER - FLA 120/60/1	15-11.7
208-240/60/1	10-6.3
SHIPPING DIMENSIONS APPROX in (mm) Width	31.5 (800)
Depth	32.87 (835)
Height	53.35 (1355)
NET WEIGHT - Ib (kg)	375 (170)
SHIPPING WEIGHT - Ib (kg)	408 (185)
AGENCY APPROVALS	cCSAus



DIMENSIONS PA25		PA25
A.	OVERALL WIDTH - in (mm)	29.53 (750)
В.	OVERALL DEPTH - in (mm)	30.91 (785)
C.	OVERALL HEIGHT - in (mm)	48.22 (1225)
D.	DOOR BOTTOM TO FLOOR - in (mm)	13.46 (342)

*Fill hoses provided to convert BSP at machine to NPT supply connection.



Ideas for the future. Answers for today.® 1.877.755.5302 | www.coinamatic.com