SPECIFICATIONS

MAT20PD TOP-LOAD WASHER





DEEP-WATER WASH SYSTEM

- Provides optimal wash performance with deep-water wash and rinse cycle options and vigorous cleaning action.
- Traditional flex-vane agitator provides four distinct wash profiles—from aggressive to gentle—designed to pull clothes from the top to the bottom of the wash basket.
- PowerWash® cycle provides more agitation, hotter water, and an extra rinse for the dirtiest loads.



INTELLIGENT CONTROLS WITH M-SERIES TECHNOLOGY

- Puts owners in charge of their profits, and provides wash-cycle flexibility to end users.
- Simple, step-by-step customized set-up allows each cycle to be priced individually.



POWERFUL DRIVE SYSTEM

- Enhanced design of the triple-lip seal and stainless-steel shaft, in addition to the premium bearings, delivers reliability and consistency.
- Powerful ½-HP PSC motor and quadgear transmission create an efficient wash for every load.



HEAVY-DUTY CABINET

- Possesses the strength needed for high-demand commercial environments.
- Sturdy front panel, side panels, and easy-access base are all manufactured from high-grade, extra-strength galvanized steel.









SPECIFICATIONS

MAT20PD TOP-LOAD WASHER



MAYTAG® COMMERCIAL TOP-LOAD WASHER

INTELLIGENT CONTROLS, COIN-DROP

WASHER SPECIFICATIONS	
MODEL	MAT20PDAGW / DOMESTIC
MOTOR SIZE — HP (KW)	1/2 (.37)
MODIFIED ENERGY FACTOR (MEF _{J2})*	1.6
INTEGRATED WATER FACTOR (IWF)*	5.46
APPROXIMATE WATER USAGE	
Average Total Water Usage Per Cycle — Gallons (liters)*	17.85 (67.6)
Average Hot Water Usage, Warm Water Cycle — Gallons (liters)	.56 (2.1)
Average Hot Water Usage, Hot Water Cycle — Gallons (liters)	7.03 (26.6)
EXTRACT SPEED — MAX G-FORCE / MAX RPM	144 / 700
CAPACITY	
Cylinder Volume — cu. ft. (liters)	3.27 (92.6)
Cylinder Diameter — in. (mm)	20.8 (528)
Cylinder Depth — in. (mm)	23.8 (605)
DIMENSIONS	
Width — in. (mm)	27 (686)
Depth — in. (mm)	26 (660)
Height — in. (mm)	441/2 (1,130)
Lid Opening — in. (mm)	17 (432)
CRATED DIMENSIONS	
Width — in. (mm)	29 (737)
Depth — in. (mm)	27.5 (699)
Height — in. (mm)	49 (1,255)
APPROXIMATE WEIGHT	
Uncrated — lbs. (kg)	159 (72.1)
Crated — lbs. (kg)	177 (80.3)
ELECTRICAL REQUIREMENTS	
Electrical Rating — Voltage / Hz	120 / 60
Breaker / Fuse — amps	15
WATER INLET / HOSE	
Operating Pressure PSI (bar)	20 — 100 (1 — 8)
Inlet Hose Length — ft. (m)	6 (1.8)
Drain Hose Length — ft. (m)	4.2 (1.3)
WARRANTY	5-Year Limited

Dimensions are for planning purposes only. See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.

^{*}Based on 2018 United States DOE J2 Testing with factory preset cycles.





5-YEAR LIMITED WARRANTY ALL PARTS COVERED

See maytagcommerciallaundry.com for complete warranty details.



